

# TRAILBOSS

## Towbar Fitting Instructions

To Suit MITSUBISHI TRITON 4WD 87- 10/96, RATED AT 2200/100kg  
MK SERIES 11/96 – 06/06, RATED AT 1900/190kg  
(DOES NOT FIT MODEL WITH BUMPER)  
Part Number QTCL373

**NOTE:** TRITON 4WD MANUAL IS RATED LOWER AT 1500 KG.

**NOTE:** FOR 3.0L PETROL AUTO & 2.8L DIESEL MK SERIES MODELS, CUSTOMERS CAN TOW UPTO 2200KG AS LONG AS THE DOWNLOAD DOES NOT EXCEED 100KG.

1. Ensure all hardware items have been included.
2. Hold towbar up in position.
3. Aligning holes in towbar with holes inside of chassis, fit bolts, flat washers, spring washers and nuts as per sketch.
4. Fit loose angles as per sketch using 40x16 spacers on models after 10/96.
5. Tighten all bolts to torque listing below.

### RECOMMENDED ASSEMBLY TORQUE LISTING

<u>Diameter</u>	<u>Grade 8.8 Bolt</u>
	Nm
M6	9.5
M8	21.7
M10	43.4
M12	77.3
M14	121.0
M16	189.8

#### FOR TOWING PURPOSES ONLY

For towing capacity details please refer to vehicle owner's manual or to the manufacturer. Overloading can void your warranties.

